Website:<u>www.keralapsc.gov.in</u> e-mail:<u>jsrna.psc@kerala.gov.in</u>



Telephone : 0471-2546396

KERALA PUBLIC SERVICE COMMISSION

No. RA1-1/50017/2018-KPSC

Thiruvananthapuram, Dated: 03.08.2022

E-TENDER NOTICE

Invitation of E-Tender for the supply and installation of 286 (Two Hundred and Eighty Six) numbers of Personal Computers for the office use of the Kerala Public Service Commission. E-Tender in one cover system is invited from competent dealers and manufacturers for the supply and installation of 286 (Two Hundred and Eighty Six) numbers of Personal Computers in accordance with respective specifications as shown in Annexure I of the Tender document.

Sl. No	. Item Details	Quantity (No.s)	Cost of Tender form (Rs)	EMD (Rs)
1	Personal Computers	286	2500/-	Rs. 50,000/-

Tenders shall be submitted as e-tender through https://etenders.kerala.gov.in. Bidders who have enrolled in the above portal with their own digital signature certificate (DSC) can participate in the tender. For obtaining digital signature certificate (DSC) and necessary portal enrollment bidders can visit the above website. E-Tender document and other details can be obtained from the above e-portal.

Tender no.	14/2022/SN
Document download/sale start date	04/08/2022
Bid submission start date	04/08/2022
Document closing date	24/08/2022 - 5.00 pm
Date & Time of opening of tender	26/08/2022 – 2.30 pm
Cost of e-Tender & EMD (Online payment)	Payment as shown in the above table including EMD should be made as a single payment through online.
Dates upto which rates are to remain firm for acceptance	90 days
Performance security	5% of the contract value
Period of supply	within 15 days of supply Order

The bidder desiring to take part in the bid shall log in to https://etenders.kerala.gov.in and then select tender and initiate payment. Bidders will be directed to the online payment gateway page and they shall make payment as directed therein.

The e-tenders submitted by the competent dealer should definitely contain a scanned and signed copy of the declaration of product offered to supply and dealership certificate from the manufacturer.

Tenders will be opened in the online presence of each bidders or their authorized representatives who have logged in at the prescribed time of opening.

If the date fixed for opening happens to be holiday or due to net failure the tenders will be opened in the next working day at the same time.

The price of the e-tender form will be received only through online payment methods stipulated in the website.

Scanned copy of the agreement (Annexure II) in the prescribed format in Kerala Stamp paper worth Rs.200/- shall be submitted online and original shall be given to the Secretary, Kerala Public Service Commission before opening of e-tender.

The rates should be quoted in Indian Currency only.

Details with respect to the e-tender and the details of specifications (Annexure I) of the item to be supplied can be obtained from the e-tender website https://etenders.kerala.gov.in.

The Secretary, Kerala Public Service Commission, Pattom will scrutinise the tenders received and will take necessary action for the award of contract.

The right of acceptance or rejection of any e-tender in full or in part without assigning any reasons thereof is reserved with the Secretary, Kerala Public Service Commission.

The rules and regulations prescribed for e-tenders by the Government of Kerala, shall be applicable to this e-tender also.

Terms and Conditions:

- 1. The make, model, year of manufacture etc of the Personal Computers shall be clearly mentioned.
- 2. All charges, taxes, duties and levies should be clearly indicated.
- 3. The items should be supplied to the office of the Kerala Public Service Commission, Pattom, Thiruvananthapuram-4 at the expense of the Tenderer.
- 4. The Product should be supplied within 15 days from the date of Purchase Order, otherwise the tender will be cancelled without any prior intimation.

- 5. The installation, commission and initial operation to the satisfaction of the KPSC will be the responsibility of the supplier.
- 6. The payment will be made after completion of supply, installation and commission subject to the certification by our Technical Experts as to the quality and efficiency of the item supplied.
- 7. In case of under performance during the warranty period, the item should be replaced and period of warranty will recommence from the date of replacement.
- 8. The successful bidder should remit , 5% of the contract value as performance Security in favour of Secretary, K.P.S.C Thiruvananthapuram. The Performance Security Deposit will be released after the expiry of Warranty Period.
- 9. Any legal disputes that may arise in relation to the e-tender formalities will be restricted to jurisdiction of Thiruvananthapuram District.

The communications should be addressed to : The Secretary, Kerala Public Service Commission Pattom,Thiruvananthapuram Kerala-695004

Sd/-SAJU GEORGE SECRETARY, KERALA PUBLIC SERVICE COMMISSION

Note:- More details can be had from the office of Additional Secretary, R&A wing, Kerala Public Service Commission.Pattom,Thiruvananthapuram-4.

ANNEXURE-1

4RAM4 GB DDR4 RAM 3200MHz expandable up to 64 GB with Min. 2 DIMM Slots5Hard drive500GB SATA 7200rpm HDD6GraphicsIntegrated Intel HD Graphics7SlotsMinimum 2 M.2 Slot & 1 SATA Slot8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU		Specification for Personal Computers (236 Nos)		
1Intel® Celeron® G6900T, 4MB, 2 cores, 2 threads, up to 2.80GHz, 35WIntel® Celeron® G6900T, 4MB, 2 cores, 2 threads, up to 2.80GHz, 35W2ChipsetIntel® B660 or better3MotherboardOEM Motherboard with embedded Discrete (Hardware) TPM 2.04RAM4 GB DDR4 RAM 3200MHz expandable up to 64 GB with Min. 2 DIMM Slots5Hard drive500GB SATA 7200rpm HDD6GraphicsIntegrated Intel HD Graphics7SlotsMinimum 2 M.2 Slot & 1 SATA Slot8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 2 button Optical Scroll mouse (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password, USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chass				
1Processor2.80GHz, 35WIntel® Celeron® G6900T, 4MB, 2 cores, 2 threads, up to 2.80GHz, 35W2ChipsetIntel® B660 or better3MotherboardOEM Motherboard with embedded Discrete (Hardware) TPM 2.04RAM4 GB DDR4 RAM 3200MHz expandable up to 64 GB with Min. 2 DIMM Slots5Hard drive500GB SATA 7200rpm HDD6GraphicsIntegrated Intel HD Graphics7SlotsMinimum 2 M.2 Slot & 1 SATA Slot8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password, USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount	S.No	Item	*	
3MotherboardOEM Motherboard with embedded Discrete (Hardware) TPM 2.04RAM4 GB DDR4 RAM 3200MHz expandable up to 64 GB with Min. 2 DIMM Slots5Hard drive500GB SATA 7200rpm HDD6GraphicsIntegrated Intel HD Graphics7SlotsMinimum 2 M.2 Slot & 1 SATA Slot8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO C	1	Processor	2.80GHz, 35WIntel [®] Celeron [®] G6900T, 4MB, 2 cores, 2 threads, up to	
4GB DDR4 RAM 3200MHz expandable up to 64 GB with Min. 2 DIMM Slots5Hard drive500GB SATA 7200rpm HDD6GraphicsIntegrated Intel HD Graphics7SlotsMinimum 2 M.2 Slot & 1 SATA Slot8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	2	Chipset	Intel® B660 or better	
4RAM2 DIMM Slots5Hard drive500GB SATA 7200rpm HDD6GraphicsIntegrated Intel HD Graphics7SlotsMinimum 2 M.2 Slot & 1 SATA Slot8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password, USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	3	Motherboard	OEM Motherboard with embedded Discrete (Hardware) TPM 2.0	
6GraphicsIntegrated Intel HD Graphics7SlotsMinimum 2 M.2 Slot & 1 SATA Slot8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	4	RAM	1 I	
7SlotsMinimum 2 M.2 Slot & 1 SATA Slot8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	5	Hard drive	500GB SATA 7200rpm HDD	
8AudioIntegrated audio controller9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).17SupportThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	6	Graphics	Integrated Intel HD Graphics	
9NICOn-board 10/100/1000 Mbps NIC supports Netboot (PXE)10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password, USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	7	Slots	Minimum 2 M.2 Slot & 1 SATA Slot	
10KeyboardOEM 104 Keys Keyboard (Same make as PC)11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	8	Audio	Integrated audio controller	
11MouseOEM 2 button Optical Scroll mouse (Same make as PC)12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	9	NIC	On-board 10/100/1000 Mbps NIC supports Netboot (PXE)	
12USB PortsTotal 6 USB Ports with minimum 4 USB 3.2 or better13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	10	Keyboard	OEM 104 Keys Keyboard (Same make as PC)	
13Other PortsMinimum 1 DP, 1 HDMI Port & 1 VGA, 1 RJ45 Port, 1 Universal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	11	Mouse	OEM 2 button Optical Scroll mouse (Same make as PC)	
13Other PortsUniversal Audio jack.14SecurityDiscrete TPM 2.0, Tool less Chassis with Intrusion Switch, 1 Kensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	12	USB Ports	Total 6 USB Ports with minimum 4 USB 3.2 or better	
14SecurityKensington security-cable slot15BIOSConfiguration Tool to Enable these features in a single tool power on password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	13	Other Ports		
15BIOSon password, set up password , USB port disable with life cycle management tool. Supports Netboot (PXE).16Information AccessibilityThe detailed Technical Specifications of the model with images should be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	14	Security		
16Accessibilityshould be available to public on OEM's official website.17SupportDrivers should be available for download from OEM site for at least 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	15	BIOS		
17Supportleast 3 years form the date of the purchases order.18Form FactorMicro Form Factor less than 1.2 Ltrs Chassis with Intrusion Switch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	16		I S	
18Form FactorSwitch. Vesa Mount kit to mount chassis behind display19Power SupplyMaximum 65W external PSU20Monitor19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	17	Support		
20 Monitor 19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	18	Form Factor		
20 Monitor Monitor. Display and CPU should be from the same OEM	19	Power Supply	Maximum 65W external PSU	
21 OS Certification Ubuntu Linux	20	Monitor	19" inch or above, Resolution -1366x768 or higher TCO Certified Monitor. Display and CPU should be from the same OEM	
	21	OS Certification	Ubuntu Linux	

22	General Certification	Energy Star 6.0, MIL STD 810 G Test Passed, TCO for Monitor, RoHS, EPEAT India Registered, FCC, ISO 9001:2013 or higher
23	Operating System	Ubuntu Linux 22.04 LTS
24	Accessories	With required connecting cables
25	Warranty	Five Years Comprehensive on-site OEM warranty (including Monitor, Keyboard, Mouse, Power Adapter)
26	MAF	Manufacturer Authorization Required